

## T084 Standard Wax

An excellent standard wax quality offering optimum cost benefits. This high quality ribbon covers all general purpose requirements expected from a wax ribbon for a solid performance on paper substrates. It provides clear, crisp barcodes – standard, rotated or 2-D on a variety of paper stocks. The back coat has a very low friction co-efficient and contains an anti-static additive to prolong the life of the print head.

General Item Data		
<b>Film Thickness</b>	:	<b>4.5µm</b>
<b>Print Speed</b>	:	<b>8" = 200mm/s</b>
<b>Print Energy</b>	:	<b>Low - Medium</b>

Substrate Application Range			
<b>Vellum</b>	✓	<b>Tag Board</b>	✓
<b>Uncoated</b>	✓	<b>Matt Coated</b>	✓
<b>Semi Gloss</b>	✓	<b>Gloss Coated</b>	✓

Characteristics Level										
<b>Chemical Resistance</b>	1	2	3	4	5	6	7	8	9	10
<b>Durability</b>	1	2	3	4	5	6	7	8	9	10
<b>Substrate Versatility</b>	1	2	3	4	5	6	7	8	9	10
<b>Print Energy</b>	1	2	3	4	5	6	7	8	9	10
<b>Print Speed</b>	1	2	3	4	5	6	7	8	9	10

Revision C

**1 = Low      10 = High**

These tests are performed using standard Zhuorim test methods and the features mentioned should be used as guidelines and not taken as a guarantee. Customers are requested to assess the suitability of these products for their own use.

Storage Conditions

Product shelf life has been proven through age testing up to 24 months under the following conditions: Out of direct sunlight, storage between temperatures of 5°C to 35°C in dry conditions

A material safety datasheet or certificate is available on request. This quality is in compliance with

