

T001 Standard Wax Resin

High quality wax resin formulation designed for use on a variety of flat head printers. It has been accredited for use within the food industry to ISEGA. It is suitable for use on label face stocks ranging from paper to synthetics. The resultant print shows excellent scratch and smudge resistance, as well as a high chemical resistance. The back coat has a very low friction co-efficient and contains an anti-static additive to prolong the life of the print head.

General Item Data		
Film Thickness	:	4.5µm
Print Speed	:	8" = 200mm/s
Print Energy	:	Medium

Substrate Application Range			
Semi Gloss	✓	PE	✓
Matt Coated	✓	PET	✓
Gloss Coated	✓	PP	✓
Tag Board	✓	PVC	✓

Characteristics Level										
Chemical Resistance	1	2	3	4	5	6	7	8	9	10
Durability	1	2	3	4	5	6	7	8	9	10
Substrate Versatility	1	2	3	4	5	6	7	8	9	10
Print Energy	1	2	3	4	5	6	7	8	9	10
Print Speed	1	2	3	4	5	6	7	8	9	10

Revision B

1 = Low 10 = High

These tests are performed using standard Pelikan test methods and the features mentioned should be used as guidelines and not taken as a guarantee. Customers are requested to assess the suitability of these products for their own use.

Storage Conditions

Product shelf life has been proven through age testing up to 24 months under the following conditions : Out of direct sunlight, storage between temperatures of 5°C to 35°C in dry conditions

A material safety datasheet or certificate is available on request. This quality is in compliance with

