

T056 Universal Wax

Highly versatile enhanced universal wax grade for use on flat head and some near edge printers which gives outstanding print performance on plain and coated paper through to synthetic substrates. The added durability of this enhanced wax grade can also satisfy more demanding applications. A high quality and performance thermal transfer ribbon offering optimum cost benefits. The back coat has a very low friction co-efficient and contains an anti-static additive to prolong the life of the print head.

General Item Data		
Film Thickness	:	4.5µm
Print Speed	:	8" = 200mm/s
Print Energy	:	Low - Medium

Substrate Application Range			
Vellum	✓	Tag Board	✓
Uncoated	✓	Matt Coated	✓
Semi-Gloss	✓	Gloss Coated	✓

Characteristics Level										
Chemical Resistance	1	2	3	4	5	6	7	8	9	10
Durability	1	2	3	4	5	6	7	8	9	10
Substrate Versatility	1	2	3	4	5	6	7	8	9	10
Print Energy	1	2	3	4	5	6	7	8	9	10
Print Speed	1	2	3	4	5	6	7	8	9	10

Revision C

1 = Low 10 = High

These tests are performed using standard Zhuorim test methods and the features mentioned should be used as guidelines and not taken as a guarantee. Customers are requested to assess the suitability of these products for their own use.

Storage Conditions

Product shelf life has been proven through age testing up to 24 months under the following conditions: Out of direct sunlight, storage between temperatures of 5°C to 35°C in dry conditions

A material safety datasheet or certificate is available on request. This quality is in compliance with

