

T082 Premium NE WR Green

Premium green wax resin designed for use on in-line / near edge printers. This wax resin grade shows superior print quality on a wide range of label stocks. The print has a high degree of resistance to chemicals, as well as an excellent scratch and smudge resistance. The coating is specially formulated to work in transmissive mode. The ink coating dissipates static and, coupled with the ribbon's low energy requirements, helps to prolong print head life.

| General Item Data | | |
|-------------------|---|--------------|
| Film Thickness | : | 4.5µm |
| Print Speed | : | 14" =350mm/s |
| Print Energy | : | Low - Medium |
| Pantone Colour | : | 3395M |

| Substrate Application Range | | | |
|-----------------------------|---|-----------|---|
| Vellum | ✓ | Tag Board | ✓ |
| Uncoated | ✓ | PE | ✓ |
| Semi Gloss | ✓ | PET | ✓ |
| Matt Coated | ✓ | PP | ✓ |
| Gloss Coated | ✓ | PVC | ✓ |

| Characteristics Level | | | | | | | | | | |
|-----------------------|---|---|---|---|---|---|---|---|---|----|
| Chemical Resistance | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| Durability | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| Substrate Versatility | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| Print Energy | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| Print Speed | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |

Revision B

1 = Low 10 = High

These tests are performed using standard Pelikan test methods and the features mentioned should be used as guidelines and not taken as a guarantee. Customers are requested to assess the suitability of these products for their own use.

Storage Conditions

Product shelf life has been proven through age testing up to 24 months under the following conditions : Out of direct sunlight, storage between temperatures of 5°C to 35°C in dry conditions

A material safety datasheet or certificate is available on request. This quality is in compliance with

