

T018 Wax Red

General purpose red wax grade for use on flat head printers which is designed for use on plain and coated paper label stock. It provides an economic method of producing high quality bar codes. The back coat has a very low friction co-efficient and contains an anti-static additive to prolong the life of the print head.

General Item Data		
Film Thickness	:	4.5µm
Print Speed	:	8" = 200mm/s
Print Energy	:	Medium - High
Pantone Colour	:	032M

Substrate Application Range			
Vellum	✓	Matt Coated	✓
Uncoated	✓	Gloss Coated	✓
Semi Gloss	✓		

Characteristics Level										
Chemical Resistance	1	2	3	4	5	6	7	8	9	10
Durability	1	2	3	4	5	6	7	8	9	10
Substrate Versatility	1	2	3	4	5	6	7	8	9	10
Print Energy	1	2	3	4	5	6	7	8	9	10
Print Speed	1	2	3	4	5	6	7	8	9	10

Revision B

1 = Low 10 = High

These tests are performed using standard Pelikan test methods and the features mentioned should be used as guidelines and not taken as a guarantee. Customers are requested to assess the suitability of these products for their own use.

Storage Conditions

Product shelf life has been proven through age testing up to 24 months under the following conditions : Out of direct sunlight, storage between temperatures of 5°C to 35°C in dry conditions

A material safety datasheet or certificate is available on request. This quality is in compliance with

