

## T074 Premium NE Wax Resin

This Premium wax resin on the new 4µm film is designed for use on in-line / near edge printers. This wax resin grade shows superior print quality on a wide range of label stocks. The print has a high degree of resistance to chemicals, as well as an excellent scratch and smudge resistance. The coating is also formulated to work in trans- missive mode. The ink coating dissipates static and, coupled with the ribbon’s low energy requirements, helps to prolong print head life.

General Item Data		
Film Thickness	:	4.0µm
Print Speed	:	24” = 600mm/s
Print Energy	:	Low

Substrate Application Range			
Vellum	✓	Tag Board	✓
Uncoated	✓	PE	✓
Semi Gloss	✓	PET	✓
Matt Coated	✓	PP	✓
Gloss Coated	✓	PVC	✓

Characteristics Level										
Chemical Resistance	1	2	3	4	5	6	7	8	9	10
Durability	1	2	3	4	5	6	7	8	9	10
Substrate Versatility	1	2	3	4	5	6	7	8	9	10
Print Energy	1	2	3	4	5	6	7	8	9	10
Print Speed	1	2	3	4	5	6	7	8	9	10

Revision A

**1 = Low      10 = High**

These tests are performed using standard Pelikan test methods and the features mentioned should be used as guidelines and not taken as a guarantee. Customers are requested to assess the suitability of these products for their own use.

Storage Conditions

Product shelf life has been proven through age testing up to 24 months under the following conditions: Out of direct sunlight, storage between temperatures of 5°C to 35°C in dry conditions

A material safety datasheet or certificate is available on request. This quality is in compliance with

