

T037 NE Wax Resin

Wax resin designed for use on near edge machines. This wax resin grade shows superior print quality on a wide range of label stocks. The print is resistant to chemicals such as anti-freeze and methanol, and gives medium scratch and smudge resistance. The ink coating dissipates static and, coupled with the ribbon's low energy requirements, helps to prolong print head life.

General Item Data		
Film Thickness	:	4.5µm
Print Speed	:	12" = 300mm/s
Print Energy	:	Low - Medium

Substrate Application Range			
Vellum	✓	Tag Board	✓
Uncoated	✓	PE	✓
Semi Gloss	✓	PET	✓
Matt Coated	✓	PP	✓
Gloss Coated	✓	PVC	✓

Characteristics Level										
Chemical Resistance	1	2	3	4	5	6	7	8	9	10
Durability	1	2	3	4	5	6	7	8	9	10
Substrate Versatility	1	2	3	4	5	6	7	8	9	10
Print Energy	1	2	3	4	5	6	7	8	9	10
Print Speed	1	2	3	4	5	6	7	8	9	10

Revision B

1 = Low 10 = High

These tests are performed using standard Pelikan test methods and the features mentioned should be used as guidelines and not taken as a guarantee. Customers are requested to assess the suitability of these products for their own use.

Storage Conditions

Product shelf life has been proven through age testing up to 24 months under the following conditions : Out of direct sunlight, storage between temperatures of 5°C to 35°C in dry conditions

A material safety datasheet or certificate is available on request. This quality is in compliance with

